

**In the Claims:**

**Claims 1-13 (cancelled)**

14. **(newly added)** An insert for a single-use disposable syringe having a cylinder and a stem, the insert comprising:

at least one fixing member, that allows advancement of the stem during injection of contents of the syringe and impedes its withdrawal once an injection has been given, by fixing itself to a wall of the cylinder; and

at least one perforating member with a point at its end that is capable of penetrating a plunger on the stem, thus breaking the seal with the wall intended to contain the substance for injection when there is an attempt to withdraw the stem after injection.

15. **(newly added)** The insert of claim 14 wherein the insert has a profile which is approximately "W" shaped.

16. **(newly added)** The insert of claim 15 wherein the profile has two symmetrical lateral portions and one central portion capable of settling on at least one longitudinal wall of the stem.

17. **(newly added)** The insert of claim 14 wherein the fixing member is a gaff.

18. **(newly added)** The insert of claim 17 comprising two fixing members formed as two pairs of gaffs.

19. **(newly added)** The insert of claim 14, wherein the perforating member comprises a central gaff located between two lateral gaffs.

20. **(newly added)** The insert of claim 14 wherein the insert has a profile which is approximately "V" shaped with two portions.

21. **(newly added)** The insert of claim 20 wherein each of its two portions is capable of being supported on a respective one of the longitudinal walls.

22. **(newly added)** The insert of claim 21 wherein the fixing member comprises at least one pair of gaffs.

23. **(newly added)** The insert of claim 22 wherein the fixing member comprises two pairs of gaffs.

24. **(newly added)** The insert of claim 20 wherein the perforating member comprises two lateral gaffs.

25. **(newly added)** The insert of claim 20 further comprising as at least one end plate located adjacent the fixing member to prevent manipulations.

26. **(newly added)** The insert of claim 20 wherein the at least one perforating member is located adjacent to a front one of the at least one fixing member.